

EXTINGUISHES FIRE AUTOMATICALLY...SO YOU DON'T HAVE TO!

Not a moment lost.
...even when no one's around.

Worth the investment



TORRENT SERIES AUTOMATIC EXTINGUISHERS

- 24/7 unattended fire protection
- Accepted by the Canadian Coast Guard
- Approved for use in occupied areas
- Suitable for Class A, B, & C hazards
- Simple installation and maintenance
- No residue – safe for sensitive equipment
- Self-contained – no external power necessary
- Optional manual operation



Pick up yours today...
No electrical connection or piping necessary.

Mounting hardware included!

Model	Agent Filling		Maximum Protected Space		Maximum Protected Space		Max area of coverage		Max Radial Distance	
			Class A Fires		Class B (marine application)					
No.	lb.	kg	Cu. Ft.	Cu. M.	Cu. Ft.	Cu. M.	ft ²	m ²	ft	m
SFS-06	6	2.73	139	3.94	139	3.94	92.68	8.62	13	3.96
SFM-07	7	3.18	205.3	5.81	162.16	4.59	92.68	8.61	13	3.96
SFM-09	9	4.09	283.95	7.47	208.49	5.90	92.68	8.61	13	3.96
SFM-12	12	5.45	277.99	7.87	277.99	7.87	92.68	8.61	13	3.96
SFL-15	15	6.82	439.92	12.45	347.49	9.84	92.68	8.61	13	3.96
SFL-20	20	9.09	555.99	15.74	463.32	13.12	92.68	8.61	13	3.96
SFL-24	24	10.91	555.99	15.74	555.99	15.74	92.68	8.61	13	3.96
SFX-31	31	14.09	909.17	25.74	718.15	20.33	92.29	9.04	13	3.96
SFX-36	36	16.36	972.97	27.54	833.98	23.61	92.29	9.04	13	3.96
SFX-42	42	19.09	972.97	27.54	972.97	27.54	92.29	9.04	13	3.96

SF	YY	Agent Filling	TIT	P	M
Cylinder Size	Agent Filling	Sprinkler Head Temp Rating	Pressure Switch	Manual Actuator	
SFS	06 2.7	135°F (57°C)			
SFM	07 3.2	155°F (68°C)	P: Pressure Switch	M: Manual Actuator*	
SFM	09 4.1	155°F (68°C)	S: Standard (No pressure Switch)	S: Standard (No manual Actuator)	
SFM	12 5.5	175°F (79°C)			
SFL	15 6.8				
SFL	20 9.1				
SFL	24 10.9				
SFX	31 14.1				
SFX	36 15.9	200°F (93°C)**			
SFX	42 19.1				

